



OUTDOOR COOLING WITH ULTRA COOL MIST

*Quality, Performance,
& Reliability*

***CORRIGAN'S
ULTRA COOL
APPLICATIONS***

***PATIO TRELLIS
OUTDOOR DINING
POOL SIDES
GREENHOUSES
REPTILE EXHIBITS
ZOO EXHIBITS
AMUSEMENT PARKS
THEATER EVENTS
SPORTING EVENTS
SPECIAL EFFECTS
CUSTOM
ENGINEERING***



**104 Ambrogio Drive
Gurnee, IL. 60031**

**Phone: 800-462-6478
Fax: 847-263-5944
www.corriganmist.com**



Ultra Cool is Ideal for all your outdoor application needs.

We use state of the art technology specially designed to meet any outdoor cooling application or event.

Outdoors can be more enjoyable on hot summer days with Ultra Cool systems. Corrigan guarantees quality performance and reliability, leading the way in the misting and water industry for 25 years.



HIGH PRESSURE ULTRA COOL SYSTEMS

FEATURES

- 150psi to 1000psi
- 316 Stainless steel mist bar, tees and clamps
- CAT brand Triplex pump
- ASCO brand solenoid valve
- 10in 1-micron sediment filter
- Safe, non-electric air actuated on/off switch
- Low feedwater pressure lock out with manual reset to protect pump
- Low feedwater and power indicator lights
- Adjustable system pressure
- Nozzle tees can be spaced to any desired length
- Nozzle tees can be swiveled around pipe for optimal results

SPECIFICATIONS

- 115V or 220V motor depending on pump size
- 1/2HP to 2HP pump depending on nozzle quantity
- 1/2in potable cold water supply required
- Pump Unit: 26in x 9in x 9in - Shelf or floor mount
- Mist bar: 3/8in OD tube; 316 Stainless Steel
- Tees: 3/8in x 1/8in compression; 316 Stainless Steel



LOW PRESSURE ULTRA COOL SYSTEMS

FEATURES

- 60psi to 150psi
- PVC and Delrin pipe and tees
- Procon brand pump
- ASCO brand solenoid valve
- 10in 1-micron sediment filter
- Safe, non-electric air actuated on/off switch
- Low feedwater pressure lock out with manual reset to protect pump
- Low feedwater and power indicator lights
- Adjustable system pressure
- Nozzle tees spaced every 24in
- Nozzle tees can be swiveled around pipe for optimal results

SPECIFICATIONS

- 115V motor
- 1/2HP pump
- 1/2in potable cold water supply required
- Pump Unit: 26in x 9in x 9in - Shelf or floor mount
- Mist bar: 1/2in OD PVC Tube
- Tees: 1/2in x 1/8in Delrin spaced 24in

ENGINEERING

Corrigan offers custom design services for non standard installations and applications such as aesthetic fogging, humidity and propagation.

WARRANTY

2 years parts and one year labor. Nozzle and filters are considered maintenance items and are not covered. See Corrigan's standard warranty for further details.

